



## **Installation Instructions:**

- 1. Put the generator in stop mode.
- **2.** Disconnect the positive battery terminal. (Do not reconnect the positive battery terminal until step 18.)
- **3.** Using the magnetic mounts, mount the One Link inside of the generator enclosure close to the controller. (Be sure the mounting location is away from weather exposure.)
- **4.** Connect the ring connector on the **red** wire of the battery wiring harness to the positive (+) battery terminal.
- **5.** Connect the ring connector on the **black** wire of the battery wiring harness to the negative (-) battery terminal.
- **6.** Route the **red** wire and **black** wire from the One Link I/O cable to the battery wiring harness installed in steps 4 and 5.
- **7.** Using one of the included lever wire connectors, connect the bare **black** wire from the battery wiring harness to the **black** wire from the One Link I/O cable.
- **8.** Using one of the included lever wire connectors, connect the bare **red** wire from the battery wiring harness to the **red** wire from the One Link I/O cable.
- **9.** Route the **red** wire with **white** stripe from the One Link I/O cable to Wire/Terminal 178 behind the control panel.

## Panel:

## **Parts List:**



OLM002



Lever Connectors(2)



## **Installation Instructions(cont.)**

- **10**. Route the **red** wire with **black** stripe from the One Link I/O cable to Wire/Terminal 183 behind the control panel.
- 11. Route the **white** wire from the One Link I/O cable to S15 on the Hertz Meter.
- **12**. Route the **red** wire with **white** stripe from the One Link I/O cable to S16 on the Hertz Meter.
- **13**. Mount the LTE/GPS antenna on the top of the generator.
- **14**. Connect the LTE antenna cable to the top connector on the right side of the One Link.
- **15**. Connect the GPS antenna cable to the bottom connector on the right side of the One Link.
- **16**. Plug the 15 pin connector into the bottom of the One Link, and tighten both screws using a flathead screwdriver.
- **17**. Reconnect the positive battery terminal to the battery.

At this time the One Link will power up and begin communicating with the generator. Please allow 5-10 minutes for the One Link to establish a connection to the internet. Check the activation screen or your One Link account to ensure the generator's vitals update, and the One Link is transmitting data.